

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 March 2004 (18.03.2004)

PCT

(10) International Publication Number  
**WO 2004/022288 A3**

(51) International Patent Classification<sup>7</sup>: **B23C 5/08**  
(21) International Application Number:  
PCT/US2003/027218

(74) Agents: MEENAN, Larry, R. et al.; KENNAMETAL  
INC., P. O. BOX 231, 1600 TECHNOLOGY WAY, LA-  
TROBE, PA 15650-0231 (US).

(22) International Filing Date:  
2 September 2003 (02.09.2003)

(81) Designated States (*national*): AU, BR, CA, CN, DE, GB,  
IL, IN, JP, KR, NO, NZ, PH, PL, RU, SG, US, ZA.

(25) Filing Language: English

(84) Designated States (*regional*): European patent (AT, BE,  
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,  
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(26) Publication Language: English

(30) Priority Data:  
60/407,727 3 September 2002 (03.09.2002) US

**Published:**

- with international search report
- before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

(71) Applicant (*for all designated States except US*): KEN-  
NAMETAL INC. [US/US]; P. O. BOX 231, 1600 TECH-  
NOLOGY WAY, LATROBE, PA 15650-0231 (US).


(88) Date of publication of the international search report:  
24 February 2005

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): ERICKSON,  
Robert, A. [US/US]; 1005 Pebblebrook Drive, Raleigh,  
NC 27609 (US). ANDRAS, Linn, R. [US/US]; R. R. 2,  
BOX 144AA, LIGONIER, PA 15670 (US).

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

(54) Title: TOOLHOLDER



(57) **Abstract:** A toolholder (20) comprises a body portion (32), a support member assembly (33) mounted to the body portion and an insert-receiving cartridge (36) removably received in the support member. The insert-receiving cartridge (36) includes a pocket (38) for mounting a cutting insert (40) thereon. The support member assembly (33) includes a bore and the insert-receiving cartridge (36) includes a shank capable of being received in the bore. The combination of the insert-receiving cartridge (36) and the cutting insert (40) forms a cutting tool for a particular cutting operation. In one embodiment, the cutting tools are radially mounted to a side periphery of the body portion (32) such that the vertical axis of the cutting tool is substantially parallel to the longitudinal axis (L) of the toolholder (20).